

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
9 January 2003 (09.01.2003)

PCT

(10) International Publication Number
WO 03/002480 A1

(51) International Patent Classification⁷: **C04B 35/10**

SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZM, ZW.

(21) International Application Number: PCT/US02/19483

(22) International Filing Date: 20 June 2002 (20.06.2002)

(25) Filing Language: English

(26) Publication Language: English

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(30) Priority Data:
60/301,959 28 June 2001 (28.06.2001) US

Published:
— with international search report

(71) Applicant and

(72) Inventor: HAUN, Michael, J. [US/US]; 5819 La Cuesta Drive, Santa Rosa, CA 95409 (US).

(48) Date of publication of this corrected version:
13 February 2003

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,

(15) Information about Correction:
see PCT Gazette No. 07/2003 of 13 February 2003, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR MAKING PRODUCT FROM FIBER GLASS WASTE

(57) Abstract: The invention provides a method to transform large quantities of fiber glass waste into useful ceramic products by a low-cost manufacturing process. The method consists of reducing the fiber glass waste into a glass powder; mixing the glass powder with additives into a glass-additives mixture; granulating the glass-additives mixture into granulated particles; forming the granulated particles into a green ceramic article; and heating the green ceramic article into the ceramic product. Water and clay can be included in the processing. Only one firing step is needed with a low peak firing temperature of about 700°C to about 1000°C. The method conserves energy and natural resources compared to clay-based traditional ceramic manufacturing. High-quality impervious ceramic products can be produced by the invention.

WO 03/002480 A1